



**Aviation Headset Specifications**

**H10-13.4**

The standard mono model with a five foot straight cord and dual plugs for fixed wing aircraft.



**Special Features:**

Passive  
General Aviation

FAA TSO Approved  
C57 Cat. B and C58a

**Impedance:** Standard

NRR: 23dB

<b>Earphone Type:</b>	Dynamic	<b>Noise-Canceling Mic:</b>	M-7A Amplified Electret
<b>Earphone Impedance:</b>	150 ohms(300 each; wired in parallel)	<b>Mic Impedance:</b>	50 ohms +/- 20%
<b>Earphone Sensitivity:</b>	90 dB SPL on flat plate coupler, re 1mW input @ 1KHz	<b>Mic Sensitivity:</b>	400mV RMS ±6dB into 150 ohm load @ 1kHz for 114dB SPL input
<b>Earphone Frequency Response:</b>	200-5,500 Hz	<b>Mic Freq Response:</b>	300Hz--3.5KHz per RTCA DO 214
<b>Earphone Plug:</b>	PJ-055 (.25" phone plug)	<b>Mic Plug:</b>	PJ-068 (.206" phone plug)
<b>Boom Type:</b>	Universal Flex	<b>Cord:</b>	5 ft.Straight
<b>Headpad/Hardware:</b>	Super-Soft, Double-Foam Headpad,Lightweight Hardware	<b>Weight/Headset Only:</b>	16.5 oz.

